OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

### 1 Identification

- · Product Identifier
- · Trade Name: Sequel Encore™
- · Relevant identified uses of the substance or mixture and uses advised against:

Relevant identified uses include commercial, residential and institutional applications.

- · Product Description: Engineered Stone Products
- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:

**Bedrosians** 

4285 N. Golden State Blvd.

Fresno, CA 93722

559-275-5000

· Emergency telephone number:

Ara J. Movsesian

Safety Director

559-275-5000

559-289-5160

### 2 Hazard(s) Identification

· Classification of the substance or mixture:



Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

Additional information:

Hazards exempt when in bonded form or when it cannot be released due to cutting, grinding, heating, etc.

- · Label elements:
- · Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements:

H320 Causes eye irritation.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

(Contd. on page 2)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

### Trade Name: Sequel Encore™

#### · Precautionary statements:

P201 Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. P202

Do not breathe dust/fume/gas/mist/vapors/spray. P260 Avoid breathing dust/fume/gas/mist/vapors/spray. P261

Wash thoroughly after handling. P264

Do not eat, drink or smoke when using this product. P270 P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

Call a poison center/doctor if you feel unwell. P312 Get medical advice/attention if you feel unwell. P314 If eye irritation persists: Get medical advice/attention. P337+P313

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Unknown acute toxicity:

0 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 0Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



\*1 Health = \*1 Fire = 0

REACTIVITY 0

Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

## 3 Composition/Information on Ingredients

- · Chemical characterization: Substance
- · Description: Mixture of substances listed below with non-hazardous additions.

### Dangerous Components:

Dangerous Components.			
	Quartz (SiO2)	>90%	
RTECS: VV 7330000	♦ Carc. 1A, H350; STOT RE 1, H372; ♦ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320		

Non-hazardous components:

Resins and trace minerals including: Fe<sub>2</sub>0<sub>3</sub>, Fe<sub>3</sub>0<sub>4</sub>, Ti0<sub>2</sub>, Al<sub>2</sub>0<sub>3</sub>, CaO, MgO, Na<sub>2</sub>O, K<sub>2</sub>O...

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

Trade Name: Sequel Encore™

### 4 First-Aid Measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

After inhalation:

If a cough develops the individual should seek medical attention.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in the side position for transportation.

- After skin contact: Wash with soap and water.
- · After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Not applicable for intact engineered stone products.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed:

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

### 5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: None required Non-flammable
- For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Special protective equipment for firefighters: No special measures required.
- · Additional information: This product will not burn.

### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Avoid creating excessive dust.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Clean up dust with a vacuum system with a High-efficiency particulate (HEPA) air filter vacuum or damp sweeping.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling
- · Precautions for safe handling:

When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection in the absence of effective engineering controls.

· Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

Trade Name: Sequel Encore™

- Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Do not store near acids. If engineered stone products contact some acids, damage/discoloration to the surface may occur.

- Further information about storage conditions: Shelf life is unlimited.
- · Specific end use(s): No further relevant information available.

### 8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

14808-60-7 Quartz (SiO2) (>90%)

PEL see Quartz listing

REL Long-term value: 0.05\* mg/m³

\*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025\* mg/m³

\*as respirable fraction

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.

- · Personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use of a properly fitted NIOSH/MSHA approved particulate respirator is recommended when cutting natural stone products for installation or during the removal of installed product.

Protection of hands:

Cotton or leather work gloves should be worn when cutting this product to minimize skin exposure to dust and/ or cuts.

· Eve protection:

Use dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.

#### 9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid

Color: Various colorsOdor: OdorlessOdor threshold: Not determined.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

Trade Name: Sequel Encore™

· **pH-value:** Not applicable.

· Change in condition

**Melting point/Melting range:** Not determined.

· Flash point: None

Flammability (solid, gaseous): Not determined.
 Ignition temperature: Not applicable
 Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.Vapor pressure: Not applicable.

· Density:

Relative density:Not determined.Vapor density:Not applicable.Evaporation rate:Not applicable.

· Solubility in / Miscibility with:

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not applicable. **Kinematic:** Not applicable.

• Other information: No further relevant information available.

#### 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Avoid contact with acids (e.g., Hydrochloric, acetic, hydrofluoric, etc.)
- Incompatible materials: Avoid contact with acids (e.g., Hydrochloric, acetic, hydrofluoric, etc.)
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: No data available.
- · Primary irritant effect:
- On the skin: Mild irritant effect.
- · On the eye: Mild irritant effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

### Trade Name: Sequel Encore™

Irritant

Carcinogenic

- · Carcinogenic categories:
- IARC (International Agency for Research on Cancer):

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

14808-60-7 Quartz (SiO2)	1	
· NTP (National Toxicology Program):		
14808-60-7 Quartz (SiO2)	K	
· OSHA-Ca (Occupational Safety & Health Administration):		
None of the ingredients are listed.		

### 12 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

#### 13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- Recommendation: Disposal must be made according to official regulations.

### 14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

Trade Name: Seguel Encore™

· Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

· Environmental hazards: Not applicable. · Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

UN "Model Regulation": Non-Regulated Material

### 5 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

14808-60-7 Quartz (SiO2)

· California Proposition 65:



WARNING: This product can expose you to chemicals including crystalline silica (airborne particles of respirable size) in dust created during fabrication/installation only if the product is dry cut/ground or pulverized, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

· Chemicals known to cause cancer:
14808-60-7 Quartz (SiQ2)

14808-60-7 ∣Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

14808-60-7 Quartz (SiO2)

· New Jersey Special Hazardous Substance List:

14808-60-7 Quartz (SiO2)

CA

· Pennsylvania Right-to-Know List:

14808-60-7 Quartz (SiO2)

· Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 03/12/2021 Reviewed on 03/12/2021

Trade Name: Sequel Encore™

· TLV (Threshold Limit Value established by ACGIH):

14808-60-7 Quartz (SiO2)

A2

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





· *Signal word:* Danger

· Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements:

H320 Causes eye irritation.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Contact:
- · Date of last revision/ revision number: 03/12/2021 / 2

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Reviewed on 03/12/2021 Issue date 03/12/2021

### Trade Name: Sequel Encore™

#### · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

Carc. 1A: Carcinogenicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

### \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106